

Rocket

RCKT

The Rocket portable outdoor sign system is particularly suited to pavement advertising. The base can be filled with water for stability and the spring-loaded graphic support provides the flexibility needed to handle the outdoor elements.



features and benefits:

- Single or double sided
- Three legs can be filled with water or sand
- Spring-loaded graphic support
- Ideal for contour cut custom graphics
- Dark grey base with silver/black fixings
- Kit includes: 3 hollow feet, 1 base clamp/fixings, 4 self-adhesive rings, and 1 pole spring assembly
- One year hardware warranty against manufacturers defects
- Six months graphic limited warranty

dimensions:

Hardware	Graphic
<p>Assembled unit: (without graphic) 21.6" w x 45.25" h x 21.6" d</p> <p>Weight: 4.4 lbs / 2 kg approx. when empty 17.6 lbs / 8 kg approx. when filled w/water</p> <p>Each foot holds 1 gallon of water; Feet hold 3 gallons / 6 liters of water total</p>	<p>Total visual area: 24" w x 36" h</p> <p>Refer to related graphic template for more information.</p> <p>Visit: www.exhibitors-handbook.com/graphic-templates</p>
Shipping	
<p>Shipping dimensions: 42" l x 14" h x 5" d</p> <p>Shipping weight: 9 lbs / 4.08 kg</p>	

additional information:

Recommended substrate:
1/8" coroplast plastic or similar

*For applications below 40° fahrenheit, please use sand in place of water

We are continually improving and modifying our product range and reserve the right to vary the specifications without prior notice. All dimensions and weights quoted are approximate and we accept no responsibility for variance. E&OE. See Graphic Templates for graphic bleed specifications.

Set-up




Unscrew the lid on each foot and fill with water or sand (approx. 1 gal) **1**



Slide the foot onto one half of the base clamp. Repeat for other feet. **2**



When all 3 feet are attached, slide on the other half of the base clamp. **3**



Slide the plastic insert over the pole/spring assembly. **4**



Slide the pole/spring assembly onto the base. **5**



Secure the pole/spring assembly to the base using the plastic nut. **6**



Peel off the backing paper and mount the self-adhesive rings to the unit. **7**



Simply mount graphic to the adhesive rings, repeat for double sided application. Unit is complete. **8**